## NSN 6105-00-504-0034

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-504-0034

Overall Height:
31.188 inches
Overall Length:
54.500 inches
Overall Width:
24.250 inches
Thread Length: 1.3120 inches identical ends
Taper Length:
4.8750 inches identical ends
Keyway Width:
0.7500 inches identical ends
Keyway Depth:
0.7500 inches identical ends
Shaft Diameter:
2.8750 inches identical ends
Keyway Length:
4.8750 inches identical ends
Duty Cycle:
Intermittent
Inclosure Feature:
Watertight
Winding Type:
Compound wound
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Time Interval:
30.0 minutes on
Cooling Method:
Ambient air
Current Rating Method:
Load
Inclosure Specificationification:
Mil-std-108
Features Provided:
Vertical mounting position
Power Rating:
50.0000 horsepower output
Taper:
1.500 per foot in inches identical ends

## **NSN 6105-00-504-0034** Direct Current Motor - Page 2 of 2



Length Of Shaft From Housing:
6.250 inches single end
Shaft Center To Mounting Surface Distance:
11.875 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:
27.750 inches
Tempurature Rating:
40.0 operating degrees celsius
Rotor Speed Rating In Rpm:
1900.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
18.500 inches
Current Rating In Amps:
181.000 single input
Connection Type And Voltage Rating In Volts:
230.0 line to neutral single input
Shaft End Characteristic:
A2 first style identical ends and a29 second style identical ends
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.