NSN 6105-00-504-1198

Direct Current Motor - Page 1 of 2

40.0 ambient degrees celsius



View Online at https://aerobasegroup.com/nsn/6105-00-504-1198

| Overall Height: |
|---|
| 24.188 inches |
| Overall Length: |
| 34.500 inches |
| Overall Width: |
| 18.250 inches |
| Keyway Width: |
| 0.5000 inches single end |
| Keyway Depth: |
| 0.2500 inches single end |
| Shaft Diameter: |
| 2.1250 inches single end |
| Shaft Rotation Direction: |
| Clockwise single end or counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Dripproof-15 deg |
| Winding Type: |
| Compound wound |
| Mounting Method: |
| Fixed base |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Cooling Method: |
| Natural convection ventilated |
| Current Rating Method: |
| Load |
| Inclosure Specificationification: |
| Mil-std-108 |
| Features Provided: |
| Vertical mounting position |
| Power Rating: |
| 20.0000 horsepower output |
| Length Of Shaft From Housing: |
| 6.688 inches single end |
| Shaft Center To Mounting Surface Distance: |
| 10.500 inches single end |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 11.250 inches |
| Tempurature Rating: |

NSN 6105-00-504-1198

Direct Current Motor - Page 2 of 2

Mil-std (military Standard):

Mil-std-108 spec.



| Rotor Speed Rating In Rpm: |
|--|
| 2830.0 single full load |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 16.750 inches |
| Current Rating In Amps: |
| 73.700 single input |
| Connection Type And Voltage Rating In Volts: |
| 230.0 line to neutral single input |
| Shaft End Characteristic: |
| A9 single style single end |
| Terminal Type And Quantity: |
| 6 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A271a0 |