

NSN 6105-00-513-9631 Direct Current Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6105-00-513-9631 **Overall Height:** 8.500 inches **Overall Length:** 13.332 inches **Overall Width:** 10.500 inches Step Length: 0.8750 inches single end **Shaft Diameter:** 1.0000 inches single end **End Application:** M110 howitzer family **Shaft Rotation Direction:** Clockwise single end **Duty Cycle:** Intermittent **Inclosure Feature:** Totally enclosed Specific Use: Drive unit, turret rotation Winding Type: Compound wound **Mounting Method:** Flange **Mounting Facility Type And Quantity:** 8 unthreaded hole Time Interval:

15.0 minutes on

Cooling Method:

Ambient air

Keyway Center To Shaft End Distance:

0.4690 inches single end

Undercut Center To Shaft End Distance:

0.1050 inches single end

Current Rating Method:

Load

Inclosure Specificationification:

Mil-std-108

Features Provided:

Electric noise suppressor and horizontal mounting position

Woodruff Key Size Designation:

6 single end

NSN 6105-00-513-9631

Direct Current Motor - Page 2 of 2

Mil-std-108 spec.



Power Rating:
5.000 horsepower output
Length Of Shaft From Housing:
1.020 inches first end
Mounting Facility Circle Diameter:
8.125 inches
Rotor Speed Rating In Rpm:
5000.0 single no load
Current Rating In Amps:
202.000 low input
Connection Type And Voltage Rating In Volts:
24.0 line to neutral single input
Shaft End Characteristic:
A28 first style single end and a11 second style single end and a12 third style single end
Test Data Document:
19207-8724474 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
1 connector, plug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A271a0
Mil-std (military Standard):