NSN 6105-00-527-8571

Overall Height: 3.375 inches Overall Length: 6.515 inches Overall Width: 3.375 inches Shaft Diameter:

Motor-tachometer Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-527-8571

O.3120 inches single end Flatted Portion Length: 0.6250 inches single end Current Type: Dc input Flat Depth: 0.0155 inches single end Inclosure Feature: Open protected Mounting Method: End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter: 2.624 inches		
O.6250 inches single end Current Type: Dc input Flat Depth: 0.0155 inches single end Inclosure Feature: Open protected Mounting Method: End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	0.3120 inches single end	
Current Type: Dc input Flat Depth: 0.0155 inches single end Inclosure Feature: Open protected Mounting Method: End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Flatted Portion Length:	
Dc input Flat Depth: 0.0155 inches single end Inclosure Feature: Open protected Mounting Method: End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	0.6250 inches single end	
Flat Depth: 0.0155 inches single end Inclosure Feature: Open protected Mounting Method: End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Current Type:	
Inclosure Feature: Open protected Mounting Method: End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Dc input	
Inclosure Feature: Open protected Mounting Method: End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Flat Depth:	
Open protected Mounting Method: End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	0.0155 inches single end	
Mounting Method: End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Inclosure Feature:	
End bell Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Open protected	
Mounting Facility Type And Quantity: 4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Mounting Method:	
4 unthreaded hole Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	End bell	
Excitor Type: Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Mounting Facility Type And Quantity:	
Self-excited Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	4 unthreaded hole	
Calibration Speed In Rpm: 1000.0 Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Excitor Type:	
Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Self-excited	
Cooling Method: Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Calibration Speed In Rpm:	
Ambient air Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	1000.0	
Calibration Voltage Output Type In Volts: 87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Cooling Method:	
87.0 dc Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Ambient air	
Torque Rating And Type: 1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Calibration Voltage Output Type In Volts:	
1.8 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	87.0 dc	
Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Torque Rating And Type:	
Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	1.8 inch-ounces stalled	
Control Field Voltage Type And Rating In Volts: 115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Inclosure Specificationification:	
115.0 dc Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Commercial	
Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Control Field Voltage Type And Rating In Volts:	
Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	115.0 dc	
Length Of Shaft From Housing: 0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Features Provided:	
0.922 inches single end Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Vertical mounting position and horizontal mounting position	
Tempurature Rating: -40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	Length Of Shaft From Housing:	
-40.0 operating degrees celsius and 85.0 operating degrees celsius Mounting Facility Circle Diameter:	0.922 inches single end	
Mounting Facility Circle Diameter:	Tempurature Rating:	
	-40.0 operating degrees celsius and 85.0 operating degrees celsius	ıs
2.624 inches	Mounting Facility Circle Diameter:	
	2.624 inches	

NSN 6105-00-527-8571

Motor-tachometer Generator - Page 2 of 2



Rotor Speed Rating In Rpm:
3500.0 single no load
Connection Type And Voltage Rating In Volts:
115.0 line to neutral single output
Shaft End Characteristic:
A5 single style single end
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A271a0