

View Online at <https://aerobasegroup.com/nsn/6105-00-539-9604>

**Overall Height:**

13.750 inches

**Overall Length:**

17.125 inches

**Overall Width:**

13.750 inches

**Keyway Width:**

0.2500 inches single end

**Keyway Depth:**

0.1250 inches single end

**Shaft Diameter:**

1.0000 inches single end

**Keyway Length:**

2.5625 inches single end

**Shaft Rotation Direction:**

Clockwise single end or counterclockwise single end

**Duty Cycle:**

Continuous

**Inclosure Feature:**

Spray tight

**Winding Type:**

Induction-squirrel cage

**Mounting Method:**

Flange

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Cooling Method:**

Ambient air

**Current Rating Method:**

Load

**Inclosure Specificationification:**

Mil-std-108

**Bearing Type:**

Annular ball

**Features Provided:**

Horizontal mounting position

**Frame Size Designation:**

224

**Power Rating:**

15.0000 horsepower output

**Length Of Shaft From Housing:**

3.625 inches single end

**Temperature Rating:**

50.0 operating degrees celsius and 45.0 ambient degrees celsius

**Mounting Facility Circle Diameter:**

12.812 inches

**Rotor Speed Rating In Rpm:**

1800.0 single no load and 1740.0 single full load

**Current Rating In Amps:**

2.400 single input

**Connection Type And Voltage Rating In Volts:**

440.0 line to neutral single input

**Shaft End Characteristic:**

A9 single style single end

**Phase:**

Three input

**Frequency In Hertz:**

60.0 input

**Test Data Document:**

81349-mil-m-1940 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A271a0

**Mil-std (military Standard):**

Mil-std-108 spec.