NSN 6105-00-548-1550

Direct Current Motor - Page 1 of 2



Overall Height:	
9.500 inches	
Overall Length:	
23.312 inches	
Overall Width:	
13.312 inches	
Thread Length:	
1.0000 inches single en	t de la companya de
Step Diameter:	
1.124 inches single end	and 1.128 inches single end
Shaft Diameter:	
1.124 inches single end	and 1.125 inches single end
Shaft Rotation Directio	n:
Clockwise single end	
Duty Cycle:	
Intermittent	
Inclosure Feature:	
Dripproof-15 deg	
Winding Type:	
Compound wound	
Mounting Method:	
Fixed base	
Mounting Facility Type	And Quantity:
4 unthreaded hole	
Time Interval:	
30.0 minutes on	
Cooling Method:	
Ambient air	
Current Rating Method	
Load	
Inclosure Specification	ification:
Commercial	
Features Provided:	
Vertical mounting positio	n
Power Rating:	
1.5000 horsepower outpo	ut
Length Of Shaft From F	lousing:
8.281 inches single end	

5.500 inches

5.000 inches single end

Shaft Center To Mounting Surface Distance:

Center To Center Distance Between Mounting Facilities Parallel To Length:

NSN 6105-00-548-1550

Direct Current Motor - Page 2 of 2

Fiig: A271a0



Tempurature Rating:
50.0 operating degrees celsius
Rotor Speed Rating In Rpm:
1750.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
8.000 inches
Current Rating In Amps:
5.700 single input
Connection Type And Voltage Rating In Volts:
250.0 line to neutral single input
Test Data Document:
81349-mil-m-2511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No