NSN 6105-00-548-2036

Direct Current Motor - Page 1 of 2

Overall Height: 70.250 inches Overall Length: 60.250 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/6105-00-548-2036

| 49.500 inches |
|---|
| Keyway Width: |
| 1.0000 inches single end |
| Keyway Depth: |
| 0.5000 inches single end |
| Shaft Diameter: |
| 4.5000 inches single end |
| Keyway Length: |
| 5.3750 inches single end |
| Shaft Rotation Direction: |
| Clockwise single end or counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Watertight |
| Winding Type: |
| Shunt wound |
| Mounting Method: |
| Fixed base |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Cooling Method: |
| Natural convection ventilated |
| Inclosure Specificationification: |
| Mil-std-108 |
| Features Provided: |
| Vertical mounting position |
| Power Rating: |
| 765.0000 horsepower output |
| Length Of Shaft From Housing: |
| 6.750 inches single end |
| Shaft Center To Mounting Surface Distance: |
| 12.000 inches single end |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 21.500 inches |
| Tempurature Rating: |
| 70.0 ambient degrees celsius and 40.0 operating degrees celsius |

NSN 6105-00-548-2036

Direct Current Motor - Page 2 of 2

Mil-std (military Standard):

Mil-std-108 spec.



| Center To Center Distance Between Mounting Facilities Parallel To Width: | |
|--|--|
| 46.500 inches | |
| Connection Type And Voltage Rating In Volts: | |
| 550.0 line to neutral single input | |
| Shaft End Characteristic: | |
| A9 single style single end | |
| Special Features: | |
| Four additional holes 1.000 in. Dia. On 4.500 by 46.500 in.Centers for mtg | |
| Terminal Type And Quantity: | |
| 6 solder lug | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A271a0 | |