## NSN 6105-00-577-3482

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-577-3482

| Overall Height:   |
|---|
| 4.500 inches  |
| Overall Length:   |
| 9.000 inches  |
| Overall Width:  |
| 4.000 inches  |
| Step Diameter:  |
| 0.4060 inches single end  |
| Shaft Diameter:   |
| 0.3750 inches single end  |
| Shaft Rotation Direction:   |
| Clockwise single end or counterclockwise single end                       |
| Duty Cycle:   |
| Continuous  |
| Inclosure Feature:  |
| Splash proof  |
| Winding Type:   |
| Compound wound  |
| Mounting Method:  |
| Fixed base  |
| Mounting Facility Type And Quantity:                                      |
| 4 unthreaded hole   |
| Current Rating Method:  |
| Load  |
| Inclosure Specificationification:   |
| Commercial  |
| Features Provided:  |
| Electric noise suppressor   |
| Power Rating:   |
| 0.3330 horsepower output  |
| Length Of Shaft From Housing:   |
| 1.500 inches single end   |
| Shaft Center To Mounting Surface Distance:                                |
| 2.625 inches single end   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.750 inches  |
| Rotor Speed Rating In Rpm:  |
| 1500.0 single full load   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.500 inches  |
| Current Rating In Amps:   |
| 20.000 single input   |

## NSN 6105-00-577-3482

Direct Current Motor - Page 2 of 2



| Connection Type And Voltage Rating In Volts | Connection T | vpe And | Voltage | Rating | ln | Volts: |
|---|--------------|---------|---------|--------|----|--------|
|---|--------------|---------|---------|--------|----|--------|

24.0 line to neutral low input or 28.0 line to neutral high input

**Shaft End Characteristic:** 

A12 single style single end

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A271a0