

View Online at <https://aerobasegroup.com/nsn/6105-00-615-9979>

Shaft Rotation Direction:

Clockwise single end or counterclockwise single end

Duty Cycle:

Continuous

Inclosure Feature:

Dripproof protected-15 deg

Specific Use:

Variable speed drive model no. Jk1; jk2; jkc; jk1-s5; jk2-s5; jk3-s5; jk1-s6; jk2-s6; jk3-s6; jk1-s7; jk2-s7; jk3-s7; jk1-w1; jk2-w1; jk3-w1; jk1-w2; jk2-w2; jk3-w2; jk1-w3; jk2-w3; jk1-w4; jk2-w4; jk3-w4

Winding Type:

Induction-split phase

Mounting Method:

Face

Mounting Facility Type And Quantity:

4 threaded stud and 4 unthreaded hole

Cooling Method:

Self-ventilated

Inclosure Specificationification:

Commercial

Features Provided:

Horizontal mounting position

Power Rating:

0.3333 horsepower output

Rotor Speed Rating In Rpm:

1725.0 single full load

Connection Type And Voltage Rating In Volts:

115.0 line to neutral single input

Shaft End Characteristic:

A5 single style single end

Phase:

Single input

Frequency In Hertz:

60.0 input

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0