NSN 6105-00-635-0183

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-635-0183 **Overall Height:** 24.250 inches **Overall Length:** 34.875 inches **Overall Width:** 19.375 inches **Thread Length:** 0.4060 inches single end Step Diameter: 1.2500 inches single end Step Length: 0.9380 inches single end **Taper Length:** 1.7500 inches single end **Keyway Width:** 0.3750 inches single end **Keyway Depth:** 0.1875 inches single end **Shaft Rotation Direction:** Counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Totally enclosed Specific Use: Main condensate pump Winding Type: Induction-squirrel cage **Mounting Method:** Flange **Mounting Facility Type And Quantity:** 4 threaded hole **Cooling Method:** Fan cooled **Current Rating Method:** Load **Inclosure Specificationification:** Mil-std-108 **Bearing Type:** Annular ball **Features Provided:**

Vertical mounting position

NSN 6105-00-635-0183

Alternating Current Motor - Page 2 of 2



Power Rating:
26.4000 horsepower output
Thread Size:
1.000 inches single end
Taper:
0.750 per foot in inches single end
Length Of Shaft From Housing:
4.000 inches single end
Tempurature Rating:
50.0 operating degrees celsius and 65.0 ambient degrees celsius
Mounting Facility Circle Diameter:
12.000 inches
Rotor Speed Rating In Rpm:
1200.0 single no load and 1175.0 single full load
Current Rating In Amps:
14.400 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a29 second style single end and a9 third style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unf single end
Terminal Type And Quantity:
3 solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.