NSN 6105-00-635-1116

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-635-1116 **Overall Height:** 29.500 inches **Overall Length:** 36.062 inches **Overall Width:** 31.125 inches Thread Length: 0.7500 inches single end **Taper Length:** 2.0000 inches single end **Keyway Width:** 0.5000 inches single end **Keyway Depth:** 0.2500 inches single end **Shaft Diameter:** 1.8750 inches single end **Keyway Length:** 2.0000 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Dripproof-15 deg Winding Type: Induction-squirrel cage **Mounting Method:** Fixed base **Mounting Facility Type And Quantity:** 4 unthreaded hole **Cooling Method:** Natural convection ventilated **Inclosure Specificationification:** Mil-std-108 **Features Provided:** Horizontal mounting position Thready Qty Per Inch (tpi): 12 single end **Power Rating:** 117.0000 horsepower output **Thread Size:**

Till Cad Oize

1.125 inches single end

NSN 6105-00-635-1116

Alternating Current Motor - Page 2 of 2



Taper:
0.625 per foot in inches single end
Length Of Shaft From Housing:
3.438 inches single end
Shaft Center To Mounting Surface Distance:
12.500 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length
18.000 inches
Tempurature Rating:
50.0 operating degrees celsius and 55.0 ambient degrees celsius
Rotor Speed Rating In Rpm:
3450.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
20.000 inches
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a29 second style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unf single end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A271a0

Mil-std-108 spec.

Mil-std (military Standard):