

View Online at <https://aerobasegroup.com/nsn/6105-00-635-1229>

**Overall Height:**

18.594 inches

**Overall Length:**

21.812 inches

**Overall Width:**

13.875 inches

**Thread Length:**

0.5000 inches single end

**Taper Length:**

1.1250 inches single end

**Keyway Width:**

0.2500 inches single end

**Keyway Depth:**

0.1250 inches single end

**Shaft Diameter:**

0.8720 inches single end

**Keyway Length:**

0.7500 inches single end

**Shaft Rotation Direction:**

Clockwise single end or counterclockwise single end

**Duty Cycle:**

Continuous

**Inclosure Feature:**

Dripproof-15 deg

**Winding Type:**

Induction-squirrel cage

**Mounting Method:**

Flange

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Cooling Method:**

Natural convection ventilated

**Current Rating Method:**

Load

**Inclosure Specification:**

Mil-std-108

**Features Provided:**

Vertical mounting position

**Thready Qty Per Inch (tpi):**

14 single end

**Power Rating:**

6.7500 horsepower output

**Thread Size:**

0.625 inches single end

**Taper:**

0.625 per foot in inches single end

**Length Of Shaft From Housing:**

2.750 inches single end

**Temperature Rating:**

50.0 operating degrees celsius and 40.0 ambient degrees celsius

**Mounting Facility Circle Diameter:**

13.000 inches

**Rotor Speed Rating In Rpm:**

1730.0 single full load

**Current Rating In Amps:**

9.500 single input

**Connection Type And Voltage Rating In Volts:**

440.0 line to neutral single input

**Shaft End Characteristic:**

A2 first style single end and a29 second style single end

**Phase:**

Three input

**Frequency In Hertz:**

60.0 input

**Thread Series Designator:**

Uns single end

**Terminal Type And Quantity:**

3 solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A271a0

**Mil-std (military Standard):**

Mil-std-108 spec.