## NSN 6105-00-635-1236

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-635-1236 **Overall Height:** 18.000 inches **Overall Length:** 21.875 inches **Overall Width:** 16.688 inches **Thread Length:** 0.6250 inches single end **Taper Length:** 1.4380 inches single end **Keyway Width:** 0.3120 inches single end **Keyway Depth:** 0.1560 inches single end **Shaft Diameter:** 1.2500 inches single end **Keyway Length:** 1.4380 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Dripproof-15 deg Winding Type: Induction-squirrel cage **Mounting Method:** Flange **Mounting Facility Type And Quantity:** 4 unthreaded hole **Cooling Method:** Self-ventilated

Self-ventilated

Current Rating Method:
Load
Inclosure Specificationification:
Mil-std-108
Bearing Type:
Annular ball
Features Provided:
Vertical mounting position
Thready Qty Per Inch (tpi):
12 single end

## NSN 6105-00-635-1236

Alternating Current Motor - Page 2 of 2



Power Rating:
10.0000 horsepower output
Thread Size:
0.750 inches single end
Taper:
0.500 per foot in inches single end
Length Of Shaft From Housing:
3.375 inches single end
Tempurature Rating:
50.0 operating degrees celsius and 70.0 ambient degrees celsius
Mounting Facility Circle Diameter:
16.000 inches
Rotor Speed Rating In Rpm:
1735.0 single full load
Current Rating In Amps:
15.300 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a29 second style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.