

View Online at <https://aerobasegroup.com/nsn/6105-00-635-1293>

**Overall Height:**

19.375 inches

**Overall Length:**

35.000 inches

**Overall Width:**

24.187 inches

**Thread Length:**

0.5000 inches single end

**Step Diameter:**

1.2500 inches single end

**Step Length:**

1.3750 inches single end

**Taper Length:**

1.8120 inches single end

**Keyway Width:**

0.2500 inches single end

**Keyway Depth:**

0.1250 inches single end

**Keyway Length:**

1.4375 inches single end

**Shaft Rotation Direction:**

Counterclockwise single end

**Duty Cycle:**

Continuous

**Inclosure Feature:**

Totally enclosed

**Specific Use:**

Main condensate pump

**Winding Type:**

Induction-squirrel cage

**Mounting Method:**

Flange

**Mounting Facility Type And Quantity:**

4 threaded hole

**Cooling Method:**

Fan cooled

**Current Rating Method:**

Load

**Inclosure Specificationification:**

Mil-std-108

**Bearing Type:**

Annular ball

**Features Provided:**

Vertical mounting position

**Power Rating:**

25.0000 horsepower output

**Thread Size:**

0.625 inches single end

**Taper:**

0.600 per foot in inches single end

**Length Of Shaft From Housing:**

4.375 inches single end

**Temperature Rating:**

50.0 operating degrees celsius and 60.0 ambient degrees celsius

**Mounting Facility Circle Diameter:**

12.000 inches

**Rotor Speed Rating In Rpm:**

1200.0 single no load and 1175.0 single full load

**Current Rating In Amps:**

34.800 single input

**Connection Type And Voltage Rating In Volts:**

440.0 line to neutral single input

**Shaft End Characteristic:**

A2 first style single end and a29 second style single end and a12 third style single end

**Phase:**

Three input

**Frequency In Hertz:**

60.0 input

**Test Data Document:**

81349-mil-m-17060a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc single end

**Terminal Type And Quantity:**

3 solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A271a0

**Mil-std (military Standard):**

Mil-std-108 spec.