## NSN 6105-00-635-1293

Alternating Current Motor - Page 1 of 2



- internating Carrotte motor in ago in the
View Online at https://aerobasegroup.com/nsn/6105-00-635-1293
Overall Height:
19.375 inches
Overall Length:
35.000 inches
Overall Width:
24.187 inches
Thread Length:
0.5000 inches single end
Step Diameter:
1.2500 inches single end
Step Length:
1.3750 inches single end
Taper Length:
1.8120 inches single end
Keyway Width:
0.2500 inches single end
Keyway Depth:
0.1250 inches single end
Keyway Length:
1.4375 inches single end
Shaft Rotation Direction:
Counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Totally enclosed
Specific Use:
Main condensate pump
Winding Type:
Induction-squirrel cage
Mounting Method:
Flange
Mounting Facility Type And Quantity:
4 threaded hole
Cooling Method:
Fan cooled
Current Rating Method:
Load

Mil-std-108

**Bearing Type:** 

**Inclosure Specificationification:** 

Annular ball

## NSN 6105-00-635-1293

Mil-std-108 spec.

Alternating Current Motor - Page 2 of 2



Features Provided:
Vertical mounting position
Power Rating:
25.0000 horsepower output
Thread Size:
0.625 inches single end
Taper:
0.600 per foot in inches single end
Length Of Shaft From Housing:
4.375 inches single end
Tempurature Rating:
50.0 operating degrees celsius and 60.0 ambient degrees celsius
Mounting Facility Circle Diameter:
12.000 inches
Rotor Speed Rating In Rpm:
1200.0 single no load and 1175.0 single full load
Current Rating In Amps:
34.800 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a29 second style single end and a12 third style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Test Data Document:
81349-mil-m-17060a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single end
Terminal Type And Quantity:
3 solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):