NSN 6105-00-635-2205

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-635-2205 **Overall Height:** 25.250 inches **Overall Length:** 35.250 inches **Overall Width:** 24.875 inches Thread Length: 0.5000 inches single end **Taper Length:** 2.0000 inches single end **Keyway Width:** 1.5000 inches single end **Keyway Depth:** 0.1875 inches single end **Shaft Diameter:** 1.5000 inches single end **Keyway Length:** 1.5000 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Totally enclosed Winding Type: Induction-squirrel cage **Mounting Method:** Flange **Mounting Facility Type And Quantity:** 8 unthreaded hole **Cooling Method:** Fan cooled **Current Rating Method:** Load **Inclosure Specificationification:** Mil-std-108 **Bearing Type:** Annular ball Thready Qty Per Inch (tpi):

Features Provided: Vertical mounting position 18 single end

NSN 6105-00-635-2205

Alternating Current Motor - Page 2 of 2



| Power Rating: |
|---|
| 15.0000 horsepower output |
| Thread Size: |
| 0.562 inches single end |
| Taper: |
| 0.750 per foot in inches single end |
| Length Of Shaft From Housing: |
| 3.000 inches single end |
| Tempurature Rating: |
| 50.0 operating degrees celsius and 40.0 ambient degrees celsius |
| Mounting Facility Circle Diameter: |
| 16.000 inches |
| Rotor Speed Rating In Rpm: |
| 1200.0 single no load and 1140.0 single full load |
| Current Rating In Amps: |
| 21.000 single input |
| Connection Type And Voltage Rating In Volts: |
| 440.0 line to neutral single input |
| Shaft End Characteristic: |
| A2 first style single end and a29 second style single end |
| Phase: |
| Three input |
| Frequency In Hertz: |
| 60.0 input |
| Test Data Document: |
| 81349-mil-m-17060a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unf single end |
| Terminal Type And Quantity: |
| 3 solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A271a0 |
| Mil-std (military Standard): |
| Mil-std-108 spec. |