NSN 6105-00-635-5378

Direct Current Motor - Page 1 of 2



| - | |
|---|--|
| View Online at https://aerobasegroup.com/nsn/6105-00-635-5378 | |
| Overall Height: | |
| 26.500 inches | |
| Overall Length: | |
| 55.000 inches | |
| Overall Width: | |
| 37.500 inches | |
| Thread Length: | |
| 1.7500 inches identical ends | |
| Taper Length: | |
| 5.2500 inches identical ends | |
| Keyway Width: | |
| 0.8750 inches identical ends | |
| Keyway Depth: | |
| 0.4380 inches identical ends | |
| Shaft Diameter: | |
| 3.6250 inches identical ends | |
| Duty Cycle: | |
| Continuous | |
| Inclosure Feature: | |
| Dripproof-15 deg | |
| Winding Type: | |
| Compound wound | |
| Mounting Method: | |
| Fixed base | |
| Mounting Facility Type And Quantity: | |
| 4 unthreaded hole | |
| Cooling Method: | |
| Self-ventilated | |
| Current Rating Method: | |
| Load | |
| Inclosure Specificationification: | |
| Mil-std-108 | |
| Features Provided: | |
| Vertical mounting position | |
| Power Poting | |

Power Rating:

100.0000 horsepower output

Taper:

1.250 per foot in inches identical ends

Length Of Shaft From Housing:

7.000 inches second end

Shaft Center To Mounting Surface Distance:

13.375 inches single end

NSN 6105-00-635-5378

Direct Current Motor - Page 2 of 2



| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|---|
| 28.500 inches |
| Tempurature Rating: |
| 50.0 ambient degrees celsius and 40.0 operating degrees celsius |
| Rotor Speed Rating In Rpm: |
| 825.0 single full load |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 22.500 inches |
| Current Rating In Amps: |
| 367.000 single input |
| Connection Type And Voltage Rating In Volts: |
| 230.0 line to neutral single input |
| Shaft End Characteristic: |
| A2 first style identical ends and a29 second style identical ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

Mil-std-108 spec.

Mil-std (military Standard):

A271a0