## NSN 6105-00-635-5378

Direct Current Motor - Page 1 of 2



-	
View Online at https://aerobasegroup.com/nsn/6105-00-635-5378	
Overall Height:	
26.500 inches	
Overall Length:	
55.000 inches	
Overall Width:	
37.500 inches	
Thread Length:	
1.7500 inches identical ends	
Taper Length:	
5.2500 inches identical ends	
Keyway Width:	
0.8750 inches identical ends	
Keyway Depth:	
0.4380 inches identical ends	
Shaft Diameter:	
3.6250 inches identical ends	
Duty Cycle:	
Continuous	
Inclosure Feature:	
Dripproof-15 deg	
Winding Type:	
Compound wound	
Mounting Method:	
Fixed base	
Mounting Facility Type And Quantity:	
4 unthreaded hole	
Cooling Method:	
Self-ventilated	
Current Rating Method:	
Load	
Inclosure Specificationification:	
Mil-std-108	
Features Provided:	
Vertical mounting position	
Power Poting	

#### Power Rating:

100.0000 horsepower output

### Taper:

1.250 per foot in inches identical ends

### **Length Of Shaft From Housing:**

7.000 inches second end

### **Shaft Center To Mounting Surface Distance:**

13.375 inches single end

# NSN 6105-00-635-5378

Direct Current Motor - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To Length:
28.500 inches
Tempurature Rating:
50.0 ambient degrees celsius and 40.0 operating degrees celsius
Rotor Speed Rating In Rpm:
825.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
22.500 inches
Current Rating In Amps:
367.000 single input
Connection Type And Voltage Rating In Volts:
230.0 line to neutral single input
Shaft End Characteristic:
A2 first style identical ends and a29 second style identical ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std-108 spec.

Mil-std (military Standard):

A271a0