Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-635-6056

| Overall Height:                                     |
|---|
| 24.125 inches                                       |
| Overall Length:                                     |
| 43.375 inches                                       |
| Overall Width:                                      |
| 28.312 inches                                       |
| Thread Length:                                      |
| 0.5000 inches single end                            |
| Taper Length:                                       |
| 1.8750 inches single end                            |
| Keyway Width:                                       |
| 0.3750 inches single end                            |
| Keyway Depth:                                       |
| 0.1875 inches single end                            |
| Shaft Diameter:                                     |
| 1.3750 inches single end                            |
| Keyway Length:                                      |
| 1.7500 inches single end                            |
| Shaft Rotation Direction:                           |
| Clockwise single end or counterclockwise single end |
| Duty Cycle:   |
| Continuous  |
| Inclosure Feature:                                  |
| Explosion proof                                     |
| Winding Type:                                       |
| Induction-squirrel cage                             |
| Mounting Method:                                    |
| Fixed base  |
| Mounting Facility Type And Quantity:                |
| 4 unthreaded hole                                   |
| Cooling Method:                                     |
| Nonventilated                                       |
| Inclosure Specificationification:                   |
| Mil-std-108   |
| Features Provided:                                  |
| Horizontal mounting position                        |
| Thread Size:  |
| 1.000 inches single end                             |
| Taper:  |
| 0.625 per foot in inches single end                 |
| Length Of Shaft From Housing:                       |
| 10 500 inches single and                            |

10.500 inches single end

## NSN 6105-00-635-6056

Alternating Current Motor - Page 2 of 2



| 11.000 inc            | ches single end   |
|-----------------------|---|
| Center To             | OCenter Distance Between Mounting Facilities Parallel To Length |
| 16.500 inc            | hes   |
| Tempurat              | ure Rating:   |
| 40.0 opera            | ating degrees celsius and 55.0 ambient degrees celsius          |
| Center To             | Center Distance Between Mounting Facilities Parallel To Width:  |
| 18.000 inc            | hes   |
| Connectio             | on Type And Voltage Rating In Volts:                            |
| 440.0 line            | to neutral single input   |
| Shaft End             | I Characteristic:   |
| A2 first sty          | vle single end and a29 second style single end                  |
| Phase:                |   |
| Three inpu            | ut  |
| Frequenc              | y In Hertz:   |
| 60.0 input            |   |
| Thread Se             | eries Designator:   |
| Unf single            | end   |
| Terminal <sup>·</sup> | Type And Quantity:  |
| 6 wire lead           | b   |
| Shelf Life            | :   |
| N/a                   |   |
| Unit Of M             | easure:   |
|                       |   |
| Demilitari            | zation:   |
| No                    |   |
| Fiig:                 |   |
| A271a0                |   |
| Mil-std (m            | nilitary Standard):   |
| Mil-std-108           | 8 spec.   |