

NSN 6105-00-635-9620 Direct Current Motor - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/6105-00-635-9620	_
Overall Height:	
24.625 inches	
Overall Length:	
50.562 inches	
Overall Width:	
49.812 inches	
Thread Length:	
1.4375 inches identical ends	
Taper Length:	
3.7500 inches identical ends	
Keyway Width:	
0.7500 inches identical ends	
Keyway Depth:	
0.2500 inches identical ends	
Shaft Diameter:	
3.1562 inches identical ends	
Keyway Length:	
3.7500 inches identical ends	
Duty Cycle:	
Intermittent	
Inclosure Feature:	
Watertight	
Winding Type:	
Shunt wound w/commutating poles	
Mounting Method:	
Fixed base	
Mounting Facility Type And Quantity:	
4 unthreaded hole	
Time Interval:	
30.0 minutes on	
Cooling Method:	
Ambient air	
Current Rating Method:	
Load	

Inclosure Specificationification:

Mil-std-108

Features Provided:

Vertical mounting position

Frame Size Designation:

1830aey

Power Rating:

60.0000 horsepower output

NSN 6105-00-635-9620

Direct Current Motor - Page 2 of 2



Taper:	
1 300 per foot in inches	ident

1.300 per foot in inches identical ends

Length Of Shaft From Housing:

6.125 inches second end

Shaft Center To Mounting Surface Distance:

11.875 inches single end

Center To Center Distance Between Mounting Facilities Parallel To Length:

29.125 inches

Tempurature Rating:

40.0 operating degrees celsius

Rotor Speed Rating In Rpm:

575.0 single full load

Center To Center Distance Between Mounting Facilities Parallel To Width:

19.750 inches

Current Rating In Amps:

220.000 single input

Connection Type And Voltage Rating In Volts:

230.0 line to neutral single input

Shaft End Characteristic:

A2 first style identical ends and a29 second style identical ends

Test Data Document:

81349-mil-m-2511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.