NSN 6105-00-635-9718

Direct Current Motor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6105-00-635-9718



Overall Height: 25.250 inches **Overall Length:** 52.875 inches **Overall Width:** 32.374 inches **Thread Length:** 2.1250 inches identical ends **Taper Length:** 3.2500 inches identical ends **Keyway Width:** 0.7500 inches identical ends **Keyway Depth:** 0.3750 inches identical ends **Shaft Diameter:** 3.0000 inches identical ends **Keyway Length:** 3.2500 inches identical ends **Shaft Rotation Direction:** Counterclockwise identical ends **Duty Cycle:** Intermittent Inclosure Feature: Watertight Specific Use: Motor for driving towing machine Winding Type: Shunt wound **Mounting Method:** Fixed base **Mounting Facility Type And Quantity:** 4 unthreaded hole Time Interval: 30.0 minutes on **Cooling Method:** Natural convection ventilated **Current Rating Method:** Load **Inclosure Specificationification:** Mil-std-108 **Bearing Type:** Roller

NSN 6105-00-635-9718

Direct Current Motor - Page 2 of 2

Mil-std-108 spec.



Features Provided:
Vertical mounting position
Power Rating:
50.0000 horsepower output
Taper:
1.300 per foot in inches identical ends
Length Of Shaft From Housing:
6.250 inches first end
Shaft Center To Mounting Surface Distance:
12.625 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:
26.625 inches
Tempurature Rating:
55.0 ambient degrees celsius and 40.0 operating degrees celsius
Center To Center Distance Between Mounting Facilities Parallel To Width:
22.250 inches
Current Rating In Amps:
370.000 single input
Connection Type And Voltage Rating In Volts:
115.0 line to neutral single input
Shaft End Characteristic:
A2 first style identical ends and a29 second style identical ends
Test Data Document:
81349-mil-m-2511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):