NSN 6105-00-669-6431

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-669-6431

Overall Height:
8.875 inches
Overall Length:
13.313 inches
Overall Width:
8.625 inches
Shaft Diameter:
0.7500 inches single end
Shaft Rotation Direction:
Clockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Dripproof-15 deg
Winding Type:
Compound wound
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Current Rating Method:
Load
Load Inclosure Specificationification:
Inclosure Specificationification:
Inclosure Specificationification: Commercial
Inclosure Specificationification: Commercial Power Rating:
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing:
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance:
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 7.000 inches
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 7.000 inches Tempurature Rating:
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 7.000 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 7.000 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius Rotor Speed Rating In Rpm:
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 7.000 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius Rotor Speed Rating In Rpm: 1725.0 single full load
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 7.000 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width:
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 7.000 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 4.750 inches
Inclosure Specificationification: Commercial Power Rating: 0.5000 horsepower output Length Of Shaft From Housing: 1.625 inches single end Shaft Center To Mounting Surface Distance: 4.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 7.000 inches Tempurature Rating: 40.0 ambient degrees celsius and 50.0 operating degrees celsius Rotor Speed Rating In Rpm: 1725.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 4.750 inches Current Rating In Amps:

NSN 6105-00-669-6431

Direct Current Motor - Page 2 of 2



	acteristic	

A5 single style single end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0