NSN 6105-00-683-5450

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-683-5450

| Ove | erall Height: |
|------|---|
| 1.80 | 00 inches |
| Ove | erall Length: |
| 3.18 | 38 inches |
| Ove | erall Width: |
| 1.56 | 32 inches |
| Sha | ft Diameter: |
| 0.12 | 230 inches single end |
| Мах | kimum Operating Altitude Rating: |
| 500 | 00.0 feet |
| Sha | ft Rotation Direction: |
| Cloc | ckwise single end or counterclockwise single end |
| Dut | y Cycle: |
| Inte | rmittent |
| Incl | osure Feature: |
| Tota | ally enclosed |
| Win | ding Type: |
| Seri | es wound |
| Μοι | unting Method: |
| Pad | |
| Μοι | unting Facility Type And Quantity: |
| 4 ur | nthreaded hole |
| Tim | e Interval: |
| 3.0 | minutes on and 17.0 minutes off |
| Cur | rent Rating Method: |
| Loa | d |
| Pov | ver Rating: |
| 0.01 | 33 horsepower output |
| Len | gth Of Shaft From Housing: |
| 0.32 | 25 inches single end |
| Ten | npurature Rating: |
| -55. | 0 operating degrees celsius and 125.0 operating degrees celsius |
| Rot | or Speed Rating In Rpm: |
| 107 | 00.0 single full load |
| Cen | ter To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.25 | 50 inches |
| Cen | ter To Center Distance Between Mounting Facilities Parallel To Height |
| 1.25 | 50 inches |
| Cur | rent Rating In Amps: |
| 2.10 | 00 single input |
| Cor | nection Type And Voltage Rating In Volts: |
| | |

NSN 6105-00-683-5450

Direct Current Motor - Page 2 of 2

Shaft End Characteristic:

A13 single style single end

Terminal Type And Quantity:

1 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A271a0

