

View Online at <https://aerobasegroup.com/nsn/6105-00-689-3490>

Current Type:

Ac input

Inclosure Feature:

Totally enclosed

Mounting Method:

Clamp ring

Mounting Facility Type And Quantity:

1 unthreaded hole

Control Field Current Rating In Amps:

7.500

Inclosure Specification:

Mil-std-108

Control Field Voltage Type And Rating In Volts:

48.0 dc

Criticality Code Justification:

Feat

Rotor Speed Rating In Rpm:

3650.0 single no load

Connection Type And Voltage Rating In Volts:

115.0 line to neutral single input

Phase:

Three input

Special Features:

Items are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, tolerances/clearances, electronic characteristics, and metallurgical properties will be specified for government quality assurance representatives to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts; motor has double ended shaft

Frequency In Hertz:

400.0 input

Reference Number Differentiating Characteristics:

As modified by navord dwg. 2994349

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.