NSN 6105-00-801-8857

Overall Height: 14.000 inches

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-801-8857

Overall Length:
14.250 inches
Overall Width:
10.813 inches
Shaft Diameter:
1.0625 inches single end
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Dripproof-15 deg
Winding Type:
Induction-squirrel cage
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Cooling Method:
Natural convection ventilated
Keyway Center To Shaft End Distance:
0.7190 inches single end
Inclosure Specificationification:
Mil-std-108
Features Provided:
Total of Frontier.
Vertical mounting position and horizontal mounting position
Vertical mounting position and horizontal mounting position
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation:
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end Power Rating:
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end Power Rating: 2.0000 horsepower output
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end Power Rating: 2.0000 horsepower output Length Of Shaft From Housing:
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 0.000 inches single end
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 0.000 inches single end Shaft Center To Mounting Surface Distance:
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 0.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 0.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length:
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 0.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 6.750 inches
Vertical mounting position and horizontal mounting position Woodruff Key Size Designation: 6 single end Power Rating: 2.0000 horsepower output Length Of Shaft From Housing: 0.000 inches single end Shaft Center To Mounting Surface Distance: 5.500 inches single end Center To Center Distance Between Mounting Facilities Parallel To Length: 6.750 inches Tempurature Rating:

NSN 6105-00-801-8857

Alternating Current Motor - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To Width: 9.000 inches

Connection Type And Voltage Rating In Volts:

220.0 line to neutral first multiple input or 440.0 line to neutral second multiple input

Shaft End Characteristic:

A11 single style single end

Phase:

Three input

Frequency In Hertz:

60.0 input

Terminal Type And Quantity:

9 solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.