NSN 6105-00-816-5405

Control Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-816-5405

Overall Height:
1.062 inches
Overall Length:
2.125 inches
Overall Width:
1.062 inches
Spline Minor Diameter:
0.0620 inches single end
Spline Quantity:
13 single end
Shaft Diameter:
0.1247 inches single end
Current Type:
Ac input
Maximum Operating Altitude Rating:
70000.0 feet
Inclosure Feature:
Totally enclosed
Spline Length:
0.3440 inches single end
Mounting Method:
Face
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 1 clamp collar and 4 threaded hole
1 clamp collar and 4 threaded hole
1 clamp collar and 4 threaded hole Cooling Method:
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps:
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062 Control Field Winding Type:
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062 Control Field Winding Type: Two windings, parallel connected or two windings, series connected
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062 Control Field Winding Type: Two windings, parallel connected or two windings, series connected Current Rating Method:
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062 Control Field Winding Type: Two windings, parallel connected or two windings, series connected Current Rating Method: No load
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062 Control Field Winding Type: Two windings, parallel connected or two windings, series connected Current Rating Method: No load Torque Rating And Type:
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062 Control Field Winding Type: Two windings, parallel connected or two windings, series connected Current Rating Method: No load Torque Rating And Type: 0.6 inch-ounces stalled
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062 Control Field Winding Type: Two windings, parallel connected or two windings, series connected Current Rating Method: No load Torque Rating And Type: 0.6 inch-ounces stalled Inclosure Specificationification:
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062 Control Field Winding Type: Two windings, parallel connected or two windings, series connected Current Rating Method: No load Torque Rating And Type: 0.6 inch-ounces stalled Inclosure Specificationification: Commercial
1 clamp collar and 4 threaded hole Cooling Method: Nonventilated Control Field Current Rating In Amps: 0.125 and 0.062 Control Field Winding Type: Two windings, parallel connected or two windings, series connected Current Rating Method: No load Torque Rating And Type: 0.6 inch-ounces stalled Inclosure Specificationification: Commercial Control Field Voltage Type And Rating In Volts:

Length Of Shaft From Housing: 0.344 inches single end

NSN 6105-00-816-5405

Control Motor - Page 2 of 2



Tempurature Rating:
-55.0 operating degrees celsius and 95.0 operating degrees celsius
Mounting Facility Circle Diameter:
0.812 inches
Rotor Speed Rating In Rpm:
6000.0 single no load
Current Rating In Amps:
0.036 single input
Connection Type And Voltage Rating In Volts:
200.0 line to neutral single input
Shaft End Characteristic:
A14 single style single end
Phase:
Two input

Terminal Type And Quantity:

400.0 input

6 screw

Frequency In Hertz:

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A271a0