Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-847-5140

Overall Height: 15.312 inches **Overall Length:** 26.762 inches **Overall Width:** 16.750 inches **Thread Length:** 1.2500 inches single end Step Diameter: 1.1250 inches single end Step Length: 2.3120 inches single end **Keyway Width:** 0.1865 inches single end Keyway Depth: 0.0930 inches single end Shaft Diameter: 0.874 inches single end and 1.172 inches single end Keyway Length: 1.8750 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Dripproof protected-15 deg Winding Type: Induction-squirrel cage **Mounting Method:** Flange **Mounting Facility Type And Quantity:** 8 unthreaded hole **Cooling Method:** Self-ventilated Keyway Center To Shaft End Distance: 1.0620 inches single end **Current Rating Method:** Load **Inclosure Specificationification:** Mil-std-108 **Bearing Type:**

Annular ball

NSN 6105-00-847-5140 Alternating Current Motor - Page 2 of 2



F	Features Provided:
١	/ertical mounting position
F	Power Rating:
1	0.0000 horsepower output
L	ength Of Shaft From Housing:
5	5.687 inches single end
٦	Fempurature Rating:
5	50.0 operating degrees celsius
ſ	Nounting Facility Circle Diameter:
ę	0.024 inches
F	Rotor Speed Rating In Rpm:
3	3450.0 single full load
(Current Rating In Amps:
1	2.500 single input
(Connection Type And Voltage Rating In Volts:
Z	140.0 line to neutral single input
ę	Shaft End Characteristic:
ŀ	A2 first style single end and a10 second style single end and a12 third style single end
F	Phase:
٦	Three input
F	Frequency In Hertz:
6	60.0 input
٦	Ferminal Type And Quantity:
3	3 wire lead
ŝ	Shelf Life:
٢	N/a
ι	Jnit Of Measure:
-	-
[Demilitarization:
١	No
F	-iig:
ŀ	A271a0
M	Mil-std (military Standard):
Ν	/il-std-108 spec.