NSN 6105-00-866-0368

Alternating Current Motor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6105-00-866-0368

| | otation Direction: |
|-----------|--|
| | se single end or counterclockwise single end |
| Duty Cy | |
| Intermitt | |
| Inclosu | re Feature: |
| General | purpose |
| Winding | ј Туре: |
| Inductio | n-squirrel cage |
| Mountir | ng Facility Type And Quantity: |
| 2 thread | ed stud |
| Time In | terval: |
| 1.0 minu | ites on and 17.0 minutes off |
| Cooling | Method: |
| Ambient | air |
| Inclosu | re Specificationification: |
| Comme | rcial |
| Power F | Rating: |
| 0.0020 ł | norsepower output |
| Rotor S | peed Rating In Rpm: |
| 7000.0 s | single full load |
| Connec | tion Type And Voltage Rating In Volts: |
| 115.0 lir | e to neutral single input |
| Shaft E | nd Characteristic: |
| A23 sing | gle style single end |
| Phase: | |
| Single ir | iput |
| Freque | ncy In Hertz: |
| 400.0 in | put |
| Shelf Li | fe: |
| N/a | |
| Unit Of | Measure: |
| | |
| Demilita | arization: |
| No | |
| Fiig: | |
| A271a0 | |