## NSN 6105-00-878-1921

Control Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-878-1921

| Shaft Diameter:   |
|---|
| 0.1250 inches single end  |
| Current Type:   |
| Ac input  |
| Inclosure Feature:  |
| General purpose   |
| Mounting Facility Type And Quantity:  |
| 1 clamp collar  |
| Cooling Method:   |
| Ambient air   |
| Control Field Current Rating In Amps:   |
| 0.107   |
| Control Field Winding Type:   |
| Two windings, series connected  |
| Current Rating Method:  |
| No load   |
| Torque Rating And Type:   |
| 0.22 inch-ounces stalled  |
| Inclosure Specificationification:   |
| Commercial  |
|   |
| Control Field Voltage Type And Rating In Volts:   |
| 40.0 ac   |
|   |
| 40.0 ac   |
| 40.0 ac Features Provided:  |
| 40.0 ac  Features Provided:  Horizontal mounting position and vertical mounting position  |
| 40.0 ac  Features Provided:  Horizontal mounting position and vertical mounting position  Tempurature Rating:   |
| 40.0 ac  Features Provided:  Horizontal mounting position and vertical mounting position  Tempurature Rating:  -55.0 operating degrees celsius and 130.0 operating degrees celsius  |
| 40.0 ac  Features Provided: Horizontal mounting position and vertical mounting position  Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius  Rotor Speed Rating In Rpm:  |
| 40.0 ac  Features Provided: Horizontal mounting position and vertical mounting position  Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius  Rotor Speed Rating In Rpm: 6000.0 single no load  |
| 40.0 ac  Features Provided: Horizontal mounting position and vertical mounting position  Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius  Rotor Speed Rating In Rpm: 6000.0 single no load  Current Rating In Amps:   |
| 40.0 ac  Features Provided: Horizontal mounting position and vertical mounting position  Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius  Rotor Speed Rating In Rpm: 6000.0 single no load  Current Rating In Amps: 0.176 single input  |
| 40.0 ac  Features Provided: Horizontal mounting position and vertical mounting position  Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius  Rotor Speed Rating In Rpm: 6000.0 single no load  Current Rating In Amps: 0.176 single input  Connection Type And Voltage Rating In Volts:  |
| 40.0 ac  Features Provided: Horizontal mounting position and vertical mounting position  Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius  Rotor Speed Rating In Rpm: 6000.0 single no load  Current Rating In Amps: 0.176 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  |
| 40.0 ac  Features Provided: Horizontal mounting position and vertical mounting position  Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius  Rotor Speed Rating In Rpm: 6000.0 single no load  Current Rating In Amps: 0.176 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic:   |
| 40.0 ac  Features Provided: Horizontal mounting position and vertical mounting position  Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius  Rotor Speed Rating In Rpm: 6000.0 single no load  Current Rating In Amps: 0.176 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end                                       |
| 40.0 ac  Features Provided: Horizontal mounting position and vertical mounting position  Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius  Rotor Speed Rating In Rpm: 6000.0 single no load  Current Rating In Amps: 0.176 single input  Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input  Shaft End Characteristic: A14 single style single end  Phase:                               |
| Features Provided: Horizontal mounting position and vertical mounting position Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius Rotor Speed Rating In Rpm: 6000.0 single no load Current Rating In Amps: 0.176 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end Phase: Single input                                 |
| Features Provided: Horizontal mounting position and vertical mounting position Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius Rotor Speed Rating In Rpm: 6000.0 single no load Current Rating In Amps: 0.176 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end Phase: Single input Frequency In Hertz:             |
| Features Provided: Horizontal mounting position and vertical mounting position Tempurature Rating: -55.0 operating degrees celsius and 130.0 operating degrees celsius Rotor Speed Rating In Rpm: 6000.0 single no load Current Rating In Amps: 0.176 single input Connection Type And Voltage Rating In Volts: 26.0 line to neutral single input Shaft End Characteristic: A14 single style single end Phase: Single input Frequency In Hertz: 400.0 input |

--

## NSN 6105-00-878-1921

Control Motor - Page 2 of 2



Demilitarization:

No

Fiig:

A271a0