

NSN 6105-00-899-1971 Alternating Current Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6105-00-899-1971 **Overall Height:** 17.375 inches **Overall Length:** 29.125 inches **Overall Width:** 22.250 inches **Spline Minor Diameter:** 1.847 inches single end and 1.858 inches single end Spline Quantity: 31 single end **Shaft Diameter:** 1.985 inches single end and 1.990 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Intermittent **Inclosure Feature:** Spray tight Winding Type: Induction-squirrel cage Spline Length: 2.000 inches single end **Mounting Method:** Fixed base **Mounting Facility Type And Quantity:** 4 unthreaded hole Time Interval: 1.0 hours on **Cooling Method:**

Ambient air

Inclosure Specificationification:

Mil-std-108

Features Provided:

Horizontal mounting position

Power Rating:

20.0000 horsepower output

Length Of Shaft From Housing:

4.688 inches single end

Shaft Center To Mounting Surface Distance:

4.125 inches single end

Center To Center Distance Between Mounting Facilities Parallel To Length:

16.250 inches

NSN 6105-00-899-1971

Alternating Current Motor - Page 2 of 2



| Rotor Speed Rating In Rpm: |
|--|
| 1200.0 single no load and 1175.0 single full load |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 20.000 inches |
| Connection Type And Voltage Rating In Volts: |
| 440.0 line to neutral single input |
| Shaft End Characteristic: |
| A14 single style single end |
| Phase: |
| Three input |
| Frequency In Hertz: |
| 60.0 input |
| Test Data Document: |
| 10001-2120869 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| AL. |

No

Fiig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.