## NSN 6105-00-899-9032

Direct Current Motor - Page 1 of 2

Overall Length: 3.107 inches Shaft Diameter:



View Online at https://aerobasegroup.com/nsn/6105-00-899-9032

| 0.187 inches single end   |
|---|
| Teeth Quantity:   |
| 18 single end   |
| Maximum Operating Altitude Rating:  |
| 35000.0 feet  |
| Shaft Rotation Direction:   |
| Counterclockwise single end   |
| Duty Cycle:   |
| Continuous  |
| Inclosure Feature:  |
| Totally enclosed  |
| Winding Type:   |
| Series wound  |
| Mounting Method:  |
| Flange  |
| Mounting Facility Type And Quantity:  |
| 4 unthreaded hole   |
| Cooling Method:   |
| Nonventilated   |
| Current Rating Method:  |
| Load  |
| Torque Rating And Type:   |
| 1.3 inch-pounds running and 9.4 inch-pounds stalled   |
| Inclosure Specificationification:   |
| Commercial  |
| Features Provided:  |
| Frame electrically grounded and horizontal mounting position and vertical mounting position |
| Length Of Shaft From Housing:   |
| 0.350 inches single end   |
| Tempurature Rating:   |
| -40.0 operating degrees celsius and 71.0 operating degrees celsius                          |
| Current Rating In Amps:   |
| 0.300 single input  |
| Connection Type And Voltage Rating In Volts:  |
| 27.0 line to neutral single input   |
| Shaft End Characteristic:   |
| A21 single style single end   |
| Special Features:   |

0.046 in. Min and 0.048 in. Maximum diameter hole through shaft

## NSN 6105-00-899-9032

Direct Current Motor - Page 2 of 2



| Terminal                   | Type  | Δnd  | Quantity:  |  |
|----------------------------|-------|------|------------|--|
| ı <del>C</del> ı IIIIII aı | ı ype | Allu | Qualitity. |  |

2 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0