NSN 6105-00-900-1368

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-900-1368

Overall Height:
0.875 inches
Overall Length:
2.031 inches
Overall Width:
0.875 inches
Shaft Diameter:
0.1248 inches single end
Teeth Quantity:
13 single end
Maximum Operating Altitude Rating:
6000.0 feet
Shaft Rotation Direction:
Clockwise single end
Duty Cycle:
Intermittent
Inclosure Feature:
Totally enclosed
Winding Type:
Permanent magnet
Mounting Method:
Face
Mounting Facility Type And Quantity:
2 threaded hole
Time Interval:
Time Interval: 5.0 seconds on and 10.0 seconds off
5.0 seconds on and 10.0 seconds off
5.0 seconds on and 10.0 seconds off Cooling Method:
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method:
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type:
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type: 0.8 inch-ounces running
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type: 0.8 inch-ounces running Inclosure Specificationification:
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type: 0.8 inch-ounces running Inclosure Specificationification: Commercial
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type: 0.8 inch-ounces running Inclosure Specificationification: Commercial Features Provided:
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type: 0.8 inch-ounces running Inclosure Specificationification: Commercial Features Provided: Frame electrically grounded and horizontal mounting position and vertical mounting position
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type: 0.8 inch-ounces running Inclosure Specificationification: Commercial Features Provided: Frame electrically grounded and horizontal mounting position and vertical mounting position Length Of Shaft From Housing:
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type: 0.8 inch-ounces running Inclosure Specificationification: Commercial Features Provided: Frame electrically grounded and horizontal mounting position and vertical mounting position Length Of Shaft From Housing: 0.325 inches single end
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type: 0.8 inch-ounces running Inclosure Specificationification: Commercial Features Provided: Frame electrically grounded and horizontal mounting position and vertical mounting position Length Of Shaft From Housing: 0.325 inches single end Tempurature Rating:
5.0 seconds on and 10.0 seconds off Cooling Method: Nonventilated Current Rating Method: Load Torque Rating And Type: 0.8 inch-ounces running Inclosure Specificationification: Commercial Features Provided: Frame electrically grounded and horizontal mounting position and vertical mounting position Length Of Shaft From Housing: 0.325 inches single end Tempurature Rating: -55.0 operating degrees celsius and 100.0 operating degrees celsius

NSN 6105-00-900-1368

Direct Current Motor - Page 2 of 2



Rotor Speed Rating In Rpm: 9000.0 single full load **Current Rating In Amps:** 0.220 single input Connection Type And Voltage Rating In Volts: 27.5 line to neutral single input Shaft End Characteristic: A23 single style single end Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A271a0