Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-902-9831

Overall Height:
20.813 inches
Overall Length:
25.531 inches
Overall Width:
18.000 inches
Thread Length:
0.6560 inches single end
Taper Length:
1.8750 inches single end
Shaft Diameter:
1.500 inches single end and 1.878 inches single end
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Dripproof-15 deg
Winding Type:
Induction-squirrel cage
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Cooling Method:
Nonventilated
Inclosure Specificationification:
Mil-std-108
Features Provided:
Horizontal mounting position
Thready Qty Per Inch (tpi):
18 single end
Power Rating:
50.0000 horsepower output
Thread Size:
1.500 inches single end
Taper:
1.400 per foot in inches single end
Length Of Shaft From Housing:
3.406 inches single end
Shaft Center To Mounting Surface Distance:
10.000 inches single end

Alternating Current Motor - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To Length:

13.750 inches

Tempurature Rating:

50.0 operating degrees celsius

Rotor Speed Rating In Rpm:

3550.0 single full load

Center To Center Distance Between Mounting Facilities Parallel To Width:

16.000 inches

Connection Type And Voltage Rating In Volts:

440.0 line to neutral single input

Shaft End Characteristic:

A2 first style single end and a29 second style single end

Phase:

Three input

Frequency In Hertz:

60.0 input

Test Data Document:

81349-mil-m-17060 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.