# NSN 6105-00-921-5194

Direct Current Motor - Page 1 of 2





#### **Overall Height:**

3.050 inches

#### **Overall Length:**

7.760 inches

### **Overall Width:**

5.145 inches

#### Spline Minor Diameter:

0.2513 inches single end

#### Spline Quantity:

11 single end

#### Shaft Diameter:

0.375 inches single end

#### Shaft Rotation Direction:

Clockwise single end

#### Duty Cycle:

Intermittent

#### **Inclosure Feature:**

General purpose

## Winding Type:

Shunt wound

#### Spline Length:

1.140 inches single end

#### Mounting Method:

Fixed base

#### Time Interval:

45.0 seconds on

#### **Cooling Method:**

Ambient air

#### **Current Rating Method:**

Load

#### **Torque Rating And Type:**

50.0 inch-pounds starting

#### **Power Rating:**

3.000 horsepower input

#### **Criticality Code Justification:**

Spcl

#### Length Of Shaft From Housing:

1.140 inches single end

#### Shaft Center To Mounting Surface Distance:

1.525 inches single end

#### Rotor Speed Rating In Rpm:

6500.0 high full load

# NSN 6105-00-921-5194

Direct Current Motor - Page 2 of 2



**Current Rating In Amps:** 

950.000 single input

**Connection Type And Voltage Rating In Volts:** 

28.0 line to line single input

### Shaft End Characteristic:

A14 first style single end

#### **Special Features:**

Shaft material is steel, qq-s-624, comp 4130, thru hardened spline end of shaft to rockwell c45-48, rest of shaftto be rockwell c30-33; pitch=32/64 in.; pitch dia.=0.3438 in.; pressure angle=30 deg.; tooth thk.=0.0479 in.; basedia.=0.2977 in.; measuring pin dia.=0.060 in.; min. Measurement over 2 pins=0.4279 in.; Ig. Of engagement=0.630 in.

#### **Special Test Features:**

Items are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, tolerances/clearances, electronic characteristics, and metallurgical properties will bespecified for government q ar (quality assurance representatives) to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts **Shelf Life:** 

N/a

---

Unit Of Measure:

Demilitarization: Yes - demil/mli Fiig: A271a0