## NSN 6105-00-962-2512

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-00-962-2512

| Overall Height:   |
|---|
| 1.480 inches  |
| Overall Length:   |
| 2.537 inches  |
| Overall Width:  |
| 1.480 inches  |
| Shaft Diameter:   |
| 0.180 inches single end and 0.181 inches single end   |
| Teeth Quantity:   |
| 11 single end   |
| Shaft Rotation Direction:   |
| Clockwise single end or counterclockwise single end   |
| Duty Cycle:   |
| Continuous  |
| Inclosure Feature:  |
| Totally enclosed  |
| Winding Type:   |
| Permanent magnet  |
| Mounting Method:  |
| Face  |
| Mounting Facility Type And Quantity:  |
| 4 threaded hole   |
| Cooling Method:   |
| Nonventilated   |
| Full Tooth Length:  |
| 0.150 inches single end   |
| Current Rating Method:  |
| Load  |
| Torque Rating And Type:   |
| 2.5 inch-ounces stalled   |
| Inclosure Specificationification:   |
| Commercial  |
| Features Provided:  |
| Frame electrically grounded and horizontal mounting position and vertical mounting position |
| Length Of Shaft From Housing:   |
| 0.150 inches single end   |
| Rotor Speed Rating In Rpm:  |
| 16000.0 single full load  |
| Current Rating In Amps:   |
| 0.600 single input  |
| Connection Type And Voltage Rating In Volts:  |
| 14.0 line to line low input or 30.0 line to line high input                                 |

## NSN 6105-00-962-2512

Direct Current Motor - Page 2 of 2



| • | • •  |     | •   |     |     |        |
|---|------|-----|-----|-----|-----|--------|
| S | 1211 | -nd | ľ'n | ara | cta | ristic |
|   |      |     |     |     |     |        |

A17 single style single end

**Terminal Type And Quantity:** 

2 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A271a0