Alternating Current Motor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6105-00-986-8231

Maximum Operating Altitude Rating: 10000.0 feet Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: General purpose Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Cooling Method: Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: Na Unit Of Measure: Demilitarization: No	view Online at https://aerobasegroup.com/nsn/0103-00-500-0251
Shaft Rotation Direction: Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: General purpose Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Roburne Specificationification: Commercial Facures Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Sheff Life: Na Unit Of Measure: Demilitarization: No	
Clockwise single end or counterclockwise single end Duty Cycle: Continuous Inclosure Feature: General purpose Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Sheff Life: N/a Unit Of Measure: Demilitarization: No	
Duty Cycle: Continuous Inclosure Feature: General purpose Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Notor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Sheff Life: N/a Unit Of Measure: Demilitarization: No	
Continuous Inclosure Feature: General purpose Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Sheff Life: N/a Unit Of Measure: T Demilitarization: No	
Inclosure Feature: General purpose Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Duty Cycle:
General purpose Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Continuous
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Sheff Life: N/a Unit Of Measure: Demilitarization: No	Inclosure Feature:
Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Sheff Life: N/a Unit Of Measure: Demilitarization: No	General purpose
Mounting Method: Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Winding Type:
Face Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Induction-squirrel cage
Mounting Facility Type And Quantity: 4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Sheff Life: N/a Unit Of Measure: Demilitarization: No	Mounting Method:
4 unthreaded hole Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Face
Cooling Method: Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1.300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting Facility Type And Quantity:
Ambient air Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1.300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	4 unthreaded hole
Inclosure Specificationification: Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1.300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Cooling Method:
Commercial Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Ambient air
Features Provided: Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inclosure Specificationification:
Thermal protective device and horizontal mounting position and vertical mounting position Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Commercial
Power Rating: 2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Features Provided:
2.0000 horsepower output Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thermal protective device and horizontal mounting position and vertical mounting position
Rotor Speed Rating In Rpm: 1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Power Rating:
1300.0 single full load Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	2.0000 horsepower output
Connection Type And Voltage Rating In Volts: 200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization:	Rotor Speed Rating In Rpm:
200.0 line to neutral single input Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	1300.0 single full load
Phase: Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Connection Type And Voltage Rating In Volts:
Three input Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	200.0 line to neutral single input
Frequency In Hertz: 400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Phase:
400.0 input Shelf Life: N/a Unit Of Measure: Demilitarization: No	Three input
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Frequency In Hertz:
Shelf Life: N/a Unit Of Measure: Demilitarization: No	400.0 input
Unit Of Measure: Demilitarization: No	
 Demilitarization: No	N/a
 Demilitarization: No	Unit Of Measure:
No	
No	Demilitarization:
· ···	
A271a0	