NSN 6105-00-989-1981

Direct Current Motor - Page 1 of 2



Direct Outlett Motor 1 age 1 of 2
View Online at https://aerobasegroup.com/nsn/6105-00-989-1981
Overall Height:
24.500 inches
liilength:
44.500 inches
Overall Width:
24.500 inches
Taper Length:
4.7500 inches single end
Shaft Diameter:
2.7500 inches single end
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Totally enclosed
Specific Use:
U/w cargo winch rh
Winding Type:
Compound wound
Mounting Method:
Fixed base
Mounting Facility Type And Quantity:
4 unthreaded hole
Cooling Method:
Nonventilated
Current Rating Method:
Load
Inclosure Specificationification:
Commercial
Features Provided:

Frame electrically grounded and vertical mounting position

Power Rating:

50.0000 horsepower output

Taper:

0.750 per foot in inches single end

Length Of Shaft From Housing:

6.000 inches single end

Shaft Center To Mounting Surface Distance:

12.000 inches single end

Center To Center Distance Between Mounting Facilities Parallel To Length:

29.000 inches

NSN 6105-00-989-1981

Direct Current Motor - Page 2 of 2

Fiig: A271a0



Tempurature Rating:
55.0 ambient degrees celsius
Rotor Speed Rating In Rpm:
600.0 single full load
Center To Center Distance Between Mounting Facilities Parallel To Width:
19.500 inches
Current Rating In Amps:
187.000 single input
Connection Type And Voltage Rating In Volts:
230.0 line to neutral single input
Shaft End Characteristic:
A4 single style single end
Special Features:
Shaftend has 1.5 in. Lg 2 in. 8 thds per in. Rh male thds
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No