Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-030-0928

Ove	erall Width:
7.25	50 inches
Thre	ead Length:
0.90	062 inches single end
Hole	e Diameter:
0.15	562 inches single end
Step	p Diameter:
0.62	25 inches single end
Step	p Length:
1.43	375 inches single end
Key	way Width:
0.18	375 inches single end
Key	way Depth:
0.09	037 inches single end
Sha	Ift Diameter:
0.50	000 inches single end
Key	way Length:
1.43	375 inches single end
Sha	Ift Rotation Direction:
Cloc	ckwise single end or counterclockwise single end
Dut	y Cycle:
Con	tinuous
Incl	osure Feature:
Spra	ay tight
Win	iding Type:
Indu	uction-squirrel cage
Μοι	unting Method:
Fac	e
Μοι	unting Facility Type And Quantity:
4 th	readed hole
Coo	bling Method:
Fan	cooled
Cur	rent Rating Method:
Loa	d
Incl	osure Specificationification:
Mil-	std-108
Fea	tures Provided:
Hori	izontal mounting position
Frai	me Size Designation:
L56	d
Pow	ver Rating:
1 75	500 horsepower output

## NSN 6105-01-030-0928 Alternating Current Motor - Page 2 of 2



Thread Size:
0.500 inches single end
Length Of Shaft From Housing:
4.187 inches single end
Tempurature Rating:
65.0 operating degrees celsius
Mounting Facility Circle Diameter:
5.875 inches
Rotor Speed Rating In Rpm:
3600.0 single no load and 3450.0 single full load
Current Rating In Amps:
2.800 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a9 second style single end and a12 third style single end and a13 fourth style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unf single end
Terminal Type And Quantity:
3 solderless lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):
Mil-std-108 spec.