# NSN 6105-01-036-2489

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-036-2489

Thread Le	ngth:
-----------	-------

1.1562 inches single end

#### **Step Diameter:**

1.249 inches single end and 1.250 inches single end

#### Step Length:

2.8750 inches single end

## **Keyway Width:**

0.2500 inches single end

#### **Keyway Depth:**

0.1250 inches single end

#### **Shaft Diameter:**

1.249 inches single end and 1.250 inches single end

#### **Keyway Length:**

2.8750 inches single end

#### **Shaft Rotation Direction:**

Clockwise single end or counterclockwise single end

#### **Duty Cycle:**

Continuous

#### **Inclosure Feature:**

Spray tight

# Winding Type:

Induction-squirrel cage

#### **Mounting Method:**

Flange

### **Mounting Facility Type And Quantity:**

6 threaded hole

# **Cooling Method:**

Fan cooled

#### **Current Rating Method:**

Load

### **Inclosure Specificationification:**

Mil-std-108

# **Features Provided:**

Horizontal mounting position

#### Frame Size Designation:

215k

### **Length Of Shaft From Housing:**

7.000 inches single end

# **Tempurature Rating:**

65.0 operating degrees celsius

#### **Mounting Facility Circle Diameter:**

10.000 inches

# NSN 6105-01-036-2489

Alternating Current Motor - Page 2 of 2



Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a9 second style single end and a12 third style single end and a13 fourth style single end
Phase:
Three input
Frequency In Hertz:
60.0 input
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:

Mil-std (military Standard): Mil-std-108 spec.

A271a0