Motor-tachometer Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-062-4584

| Overall Length: |
|--------------------------------------------------------------------|
| 5.562 inches |
| Overall Width: |
| 2.094 inches |
| Shaft Diameter: |
| 0.156 inches single end |
| Flatted Portion Length: |
| 0.2343 inches single end |
| Current Type: |
| Ac input |
| Flat Depth: |
| 0.0218 inches single end |
| Inclosure Feature: |
| Totally enclosed |
| Mounting Method: |
| Clamp ring |
| Mounting Facility Type And Quantity: |
| 1 clamp collar |
| Excitor Type: |
| Self-excited |
| Calibration Speed In Rpm: |
| 1000.0 |
| Cooling Method: |
| Natural convection ventilated |
| Calibration Voltage Output Type In Volts: |
| 6.0 ac |
| Torque Rating And Type: |
| 0.15 inch-ounces stalled |
| Inclosure Specificationification: |
| Commercial |
| Control Field Voltage Type And Rating In Volts: |
| 50.0 ac |
| Power Rating: |
| 10.000 watts input |
| Length Of Shaft From Housing: |
| 0.500 inches single end |
| Tempurature Rating: |
| -55.0 operating degrees celsius and 55.0 operating degrees celsius |
| Rotor Speed Rating In Rpm: |
| 1500.0 single no load |
| Connection Type And Voltage Rating In Volts: |
| 115.0 line to neutral single input |
| |

Motor-tachometer Generator - Page 2 of 2



Shaft End Characteristic:

A5 single style single end

Phase:

Single input

Frequency In Hertz:

60.0 output

Terminal Type And Quantity:

12 solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A271a0