

View Online at <https://aerobasegroup.com/nsn/6105-01-063-4911>

Thread Class:

3a single end

Thread Direction:

Right-hand single end

Overall Height:

12.625 inches

Overall Length:

22.938 inches

Overall Width:

13.500 inches

Thread Length:

0.625 inches single end

Step Diameter:

0.687 inches single end and 0.688 inches single end

Step Length:

1.500 inches single end

Keyway Width:

0.188 inches single end

Keyway Depth:

0.094 inches single end

Shaft Diameter:

0.500 inches single end

Keyway Length:

1.250 inches single end

Shaft Rotation Direction:

Clockwise single end or counterclockwise single end

Duty Cycle:

Continuous

Inclosure Feature:

Totally enclosed

Winding Type:

Induction-squirrel cage

Mounting Method:

Fixed base

Mounting Facility Type And Quantity:

4 unthreaded hole

Cooling Method:

Fan cooled

Current Rating Method:

Load

Inclosure Specificationification:

Nema

Features Provided:

Horizontal mounting position

Frame Size Designation:

215cn

Power Rating:

5.000 horsepower output

Thread Size:

0.500 inches single end

Length Of Shaft From Housing:

5.875 inches single end

Shaft Center To Mounting Surface Distance:

5.250 inches single end

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.000 inches

Temperature Rating:

50.0 operating degrees celsius

Rotor Speed Rating In Rpm:

3500.0 single full load

Center To Center Distance Between Mounting Facilities Parallel To Width:

8.500 inches

Current Rating In Amps:

6.500 single input

Connection Type And Voltage Rating In Volts:

440.0 line to neutral single input

Shaft End Characteristic:

A2 first style single end and a9 second style single end and a12 third style single end

Phase:

Three input

Special Features:

Shaft end second style diameter 0.681 in.; shaft end third style diameter 0.875

Frequency In Hertz:

60.0 input

Thread Series Designator:

Unc single end

Terminal Type And Quantity:

3 solderless lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0