NSN 6105-01-067-3689

Alternating Current Motor - Page 1 of 2



С	Overall Height:
9	.000 inches
C	Overall Length:
2	2.250 inches
C	Overall Width:
1	7.500 inches
S	pline Minor Diameter:
0	.681 inches single end and 0.690 inches single end
S	pline Quantity:
1	8 single end
S	haft Diameter:
0	.789 inches single end and 0.792 inches single end
D	Outy Cycle:
С	Continuous
lr	nclosure Feature:
S	pray tight
٧	Vinding Type:
lr	nduction-split phase
S	pline Length:
0	.808 inches single end and 0.818 inches single end
N	lounting Method:
F	ixed base and face
N	lounting Facility Type And Quantity:
4	slot
C	cooling Method:
Ν	latural convection ventilated
C	Current Rating Method:
L	ocked rotor
lr	nclosure Specificationification:
N	fil-std-108
F	eatures Provided:
lr	ntegral brake and horizontal mounting position
L	ength Of Shaft From Housing:
1	.327 inches single end
N	lounting Facility Circle Diameter:
0	.375 inches
R	totor Speed Rating In Rpm:
3	250.0 single full load
c	Current Rating In Amps:

11.500 single input

Connection Type And Voltage Rating In Volts:

440.0 line to neutral single input

NSN 6105-01-067-3689

Mil-std-108 spec.

Alternating Current Motor - Page 2 of 2



Shaft End Characteristic:
A14 single style single end
Phase:
Three input
Special Features:
Input current 9.0 amps maximum for four pole conn; full load rotor speed is 1625 rpm for four pole conn
Frequency In Hertz:
60.0 input
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A271a0
Mil-std (military Standard):