## NSN 6105-01-069-5088

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-069-5088

Overall Height:
1.250 inches
Overall Length:
2.557 inches
Overall Width:
1.250 inches
Undercut Diameter:
0.177 inches single end
Shaft Diameter:
0.125 inches single end
Undercut Length:
0.009 inches single end and 0.012 inches single end
Shaft Rotation Direction:
Counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Totally enclosed
Winding Type:
Permanent magnet
Mounting Method:
Face
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 2 threaded hole
Mounting Facility Type And Quantity: 2 threaded hole Cooling Method:
Mounting Facility Type And Quantity: 2 threaded hole Cooling Method: Nonventilated
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method:  Nonventilated  Undercut Center To Shaft End Distance:
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method:  Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method:  Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end  Current Rating Method:
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method:  Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end  Current Rating Method:  Load
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method:  Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end  Current Rating Method:  Load  Torque Rating And Type:
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method:  Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end  Current Rating Method:  Load  Torque Rating And Type:  1.0 inch-ounces stalled
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method: Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end  Current Rating Method: Load  Torque Rating And Type:  1.0 inch-ounces stalled  Inclosure Specificationification:
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method: Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end  Current Rating Method: Load  Torque Rating And Type:  1.0 inch-ounces stalled  Inclosure Specificationification:  Commercial
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method: Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end  Current Rating Method: Load  Torque Rating And Type:  1.0 inch-ounces stalled  Inclosure Specificationification:  Commercial  Features Provided:
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method: Nonventilated  Undercut Center To Shaft End Distance: 0.050 inches single end  Current Rating Method: Load  Torque Rating And Type: 1.0 inch-ounces stalled  Inclosure Specificationification:  Commercial  Features Provided:  Frame electrically grounded and horizontal mounting position and vertical mounting position
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method: Nonventilated  Undercut Center To Shaft End Distance: 0.050 inches single end  Current Rating Method: Load  Torque Rating And Type: 1.0 inch-ounces stalled Inclosure Specificationification: Commercial  Features Provided: Frame electrically grounded and horizontal mounting position and vertical mounting position  Power Rating:
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method: Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end  Current Rating Method: Load  Torque Rating And Type:  1.0 inch-ounces stalled  Inclosure Specificationification:  Commercial  Features Provided: Frame electrically grounded and horizontal mounting position and vertical mounting position  Power Rating:  0.015 horsepower output
Mounting Facility Type And Quantity:  2 threaded hole  Cooling Method:  Nonventilated  Undercut Center To Shaft End Distance:  0.050 inches single end  Current Rating Method:  Load  Torque Rating And Type:  1.0 inch-ounces stalled  Inclosure Specificationification:  Commercial  Features Provided:  Frame electrically grounded and horizontal mounting position and vertical mounting position  Power Rating:  0.015 horsepower output  Length Of Shaft From Housing:

## NSN 6105-01-069-5088

Direct Current Motor - Page 2 of 2



A271a0