NSN 6105-01-116-9268

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-116-9268

Thread Class:

2a single end

Thread Direction:

Right-hand single end

Overall Height:

29.000 inches

Overall Length:

37.750 inches

Overall Width:

28.375 inches

Thread Length:

0.4380 inches single end

Taper Length:

1.3750 inches single end

Keyway Width:

0.3750 inches single end

Keyway Depth:

0.1880 inches single end

Shaft Diameter:

0.997 inches single end and 1.000 inches single end

Keyway Length:

1.3750 inches single end

Shaft Rotation Direction:

Clockwise single end or counterclockwise single end

Duty Cycle:

Continuous

Inclosure Feature:

Dripproof protected-45 deg

Winding Type:

Shunt wound

Mounting Method:

Face

Mounting Facility Type And Quantity:

8 unthreaded hole

Cooling Method:

Self-ventilated

Current Rating Method:

Load

Inclosure Specificationification:

Nema

Features Provided:

Frame electrically grounded and horizontal mounting position

NSN 6105-01-116-9268

Direct Current Motor - Page 2 of 2



Thready Qty Per Inch (tpi): 16 single end Frame Size Designation: 444vy **Power Rating:** 30.0000 horsepower output **Thread Size:** 1.000 inches single end Taper: 75.000 per foot in inches single end Length Of Shaft From Housing: 2.312 inches single end **Tempurature Rating:** 50.0 operating degrees celsius **Mounting Facility Circle Diameter:** 16.000 inches **Rotor Speed Rating In Rpm:** 1150.0 single full load **Current Rating In Amps:** 100.000 single input **Connection Type And Voltage Rating In Volts:** 250.0 line to neutral single input **Shaft End Characteristic:** A2 first style single end and a29 second style single end and a1 third style single end **Special Features:** Shaft second diameter 1.624 in. Min; 1.625 in. Max **Thread Series Designator:** Un single end **Terminal Type And Quantity:** 4 solderless lug and 4 wire lead Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A271a0