## NSN 6105-01-118-7003

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-118-7003 **Overall Height:** 24.281 inches **Overall Length:** 56.937 inches **Overall Width:** 31.640 inches **Thread Length:** 0.6250 inches single end **Taper Length:** 2.6250 inches single end **Keyway Width:** 0.3750 inches single end **Keyway Depth:** 0.2030 inches single end **Shaft Diameter:** 1.000 inches single end **Keyway Length:** 2.6250 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Intermittent **Inclosure Feature:** Dripproof protected-15 deg Winding Type: Shunt wound **Mounting Method:** Face **Mounting Facility Type And Quantity:** 8 unthreaded hole Time Interval: 10.0 minutes off **Cooling Method:** Self-ventilated **Current Rating Method:** Load **Inclosure Specificationification:** Nema **Features Provided:** Horizontal mounting position Frame Size Designation:

500vy

## **NSN 6105-01-118-7003**Direct Current Motor - Page 2 of 2



Power Rating:
150.0000 horsepower output
Thread Size:
1.000 inches single end
Taper:
0.500 per foot in inches single end
Length Of Shaft From Housing:
4.000 inches single end
Tempurature Rating:
50.0 ambient degrees celsius
Mounting Facility Circle Diameter:
14.750 inches
Rotor Speed Rating In Rpm:
1750.0 first multiple full load or 3500.0 second multiple full load
Current Rating In Amps:
485.000 single input
Connection Type And Voltage Rating In Volts:
250.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a29 second style single end and a1 third style single end
Special Features:
Shaft end second style 1.800 in. Min dia, 1.805 in. Maximum dia; shaft end third style 2.125 in. Dia
Thread Series Designator:
Unf single end
Terminal Type And Quantity:
6 solderless lug and 6 wire lead
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A271a0