NSN 6105-01-121-6972

Direct Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-121-6972

| Overall Heights | | | | | | |
|---|--|--|--|--|--|--|
| Overall Height: 1.210 inches | | | | | | |
| Overall Length: | | | | | | |
| 1.940 inches | | | | | | |
| Overall Width: | | | | | | |
| 1.210 inches | | | | | | |
| Shaft Diameter: | | | | | | |
| 0.1247 inches second end | | | | | | |
| Shaft Rotation Direction: | | | | | | |
| Clockwise single end | | | | | | |
| Inclosure Feature: | | | | | | |
| | | | | | | |
| Totally enclosed Mounting Method: | | | | | | |
| Pad | | | | | | |
| · · · · · | | | | | | |
| Mounting Facility Type And Quantity: 2 unthreaded hole | | | | | | |
| | | | | | | |
| Cooling Method: Ambient air | | | | | | |
| | | | | | | |
| Current Rating Method: Load | | | | | | |
| | | | | | | |
| Torque Rating And Type: | | | | | | |
| 3.6 inch-ounces running | | | | | | |
| Power Rating: | | | | | | |
| 15.6000 watts output | | | | | | |
| Length Of Shaft From Housing: | | | | | | |
| 0.750 inches first end | | | | | | |
| Rotor Speed Rating In Rpm: | | | | | | |
| 5000.0 single no load | | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | | | | | | |
| 0.125 inches | | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | | | | | | |
| 0.125 inches | | | | | | |
| Current Rating In Amps: | | | | | | |
| 0.600 single input | | | | | | |
| Connection Type And Voltage Rating In Volts: | | | | | | |
| 26.0 line to neutral single input | | | | | | |
| Shaft End Characteristic: | | | | | | |
| A1 single style identical ends | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 2 threaded stud | | | | | | |
| Shelf Life: | | | | | | |

N/a

NSN 6105-01-121-6972

Direct Current Motor - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A271a0