NSN 6105-01-121-8734

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-121-8734

| 0.0000000000000000000000000000000000000 |
|---|
| Overall Height: |
| 6.253 inches |
| Overall Length: |
| 11.812 inches |
| Overall Width: |
| 6.253 inches |
| Keyway Width: |
| 0.124 inches single end and 0.125 inches single end |
| Keyway Depth: |
| 0.064 inches single end and 0.069 inches single end |
| Shaft Diameter: |
| 0.499 inches single end |
| Keyway Length: |
| 2.4370 inches single end |
| Shaft Rotation Direction: |
| Clockwise single end or counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Totally enclosed |
| Specific Use: |
| Fan, vaneaxial models 1r110-75d665; 1r130-75d666 |
| Winding Type: |
| Induction-squirrel cage |
| Mounting Method: |
| Face |
| Mounting Facility Type And Quantity: |
| 4 threaded hole |
| Cooling Method: |
| Separately ventilated |
| Torque Rating And Type: |
| 28.0 inch-ounces stalled |
| Inclosure Specificationification: |
| Commercial |
| Features Provided: |
| Horizontal mounting position and vertical mounting position |
| Power Rating: |
| 0.1250 horsepower output |
| Length Of Shaft From Housing: |
| 2.812 inches single end |
| Tempurature Rating: |
| 65.0 operating degrees celsius |

NSN 6105-01-121-8734

Alternating Current Motor - Page 2 of 2



| Mounting Facility Circle Diameter: |
|---|
| 3.750 inches |
| Rotor Speed Rating In Rpm: |
| 1800.0 single no load |
| Connection Type And Voltage Rating In Volts: |
| 115.0 line to neutral single input |
| Shaft End Characteristic: |
| A9 first style single end and a1 second style single end |
| Phase: |
| Single input |
| Special Features: |
| Shaft style at 0.620 in. Min, 0.625 in. Maximum dia; style a9 has 0.500-13 unc external thread 0.810 in. Long with 0.125 in. Diameter drill |
| through hole |
| Frequency In Hertz: |
| 60.0 input |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A271a0 |
| Mil-std (military Standard): |
| Mil-m-17059 spec. |