

NSN 6105-01-123-5764 Alternating Current Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6105-01-123-5764 **Overall Height:** 10.000 inches **Overall Length:** 18.250 inches **Overall Width:** 12.375 inches Thread Length: 0.5620 inches single end **Keyway Width:** 0.1860 inches single end **Keyway Depth:** 0.094 inches single end and 0.110 inches single end **Shaft Diameter:** 0.500 inches single end **Keyway Length:** 1.438 inches single end **Shaft Rotation Direction:** Clockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Dripproof protected-15 deg Winding Type: Induction-squirrel cage **Mounting Method:** Face **Mounting Facility Type And Quantity:** 4 unthreaded hole

**Cooling Method:** 

Self-ventilated

**Current Rating Method:** 

**Torque Rating And Type:** 

10.4 foot-pounds stalled

**Inclosure Specificationification:** 

Nema

**Features Provided:** 

Vertical mounting position

Frame Size Designation:

184npz

**Power Rating:** 

3.0000 horsepower output

## **NSN 6105-01-123-5764**Alternating Current Motor - Page 2 of 2



Thread Size:
0.500 inches single end
Гарег:
0.500 per foot in inches single end
Length Of Shaft From Housing:
4.250 inches single end
Tempurature Rating:
50.0 operating degrees celsius
Mounting Facility Circle Diameter:
9.125 inches
Rotor Speed Rating In Rpm:
3600.0 single no load and 3450.0 single full load
Current Rating In Amps:
42.000 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a29 second style single end and a9 third style single end and a1 fourth style single end
Phase:
Three input
Special Features:
Shaft end second style 0.875 in. Dia; shaft end third style 1.000 in. Dia; shaft end fourth style 1.250 in. Dia; shaft end third style keyway
ength 0.812 in. Lg
Frequency In Hertz:
60.0 input
Thread Series Designator:
Jnf single end
Terminal Type And Quantity:
3 solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A271a0