NSN 6105-01-151-8538

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-151-8538

Overall Height:
6.500 inches
liilength:
12.560 inches
Overall Width:
6.500 inches
Keyway Width:
0.1880 inches single end
Keyway Depth:
0.0940 inches single end
Shaft Diameter:
0.6250 inches single end
Keyway Length:
1.2500 inches single end
End Application:
Item is used on the fresh water service pump onboard 180 ft wlb c g vessels
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Totally enclosed
Totally enclosed Winding Type:
Winding Type:
Winding Type: Induction-squirrel cage
Winding Type: Induction-squirrel cage Mounting Method:
Winding Type: Induction-squirrel cage Mounting Method: Face
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity:
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Cooling Method:
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Cooling Method: Ambient air
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Cooling Method: Ambient air Current Rating Method:
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Cooling Method: Ambient air Current Rating Method: Load
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Cooling Method: Ambient air Current Rating Method: Load Inclosure Specificationification:
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Cooling Method: Ambient air Current Rating Method: Load Inclosure Specificationification: Nema
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Cooling Method: Ambient air Current Rating Method: Load Inclosure Specificationification: Nema Features Provided:
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Cooling Method: Ambient air Current Rating Method: Load Inclosure Specificationification: Nema Features Provided: Horizontal mounting position and vertical mounting position
Winding Type: Induction-squirrel cage Mounting Method: Face Mounting Facility Type And Quantity: 4 threaded hole Cooling Method: Ambient air Current Rating Method: Load Inclosure Specificationification: Nema Features Provided: Horizontal mounting position and vertical mounting position Frame Size Designation:

1.875 inches single end

Length Of Shaft From Housing:

NSN 6105-01-151-8538Alternating Current Motor - Page 2 of 2



Shaft Center To Mounting Surface Distance:
2.938 inches single end
Tempurature Rating:
-56.0 operating degrees celsius
Mounting Facility Circle Diameter:
5.875 inches
Rotor Speed Rating In Rpm:
3450.0 single full load
Current Rating In Amps:
6.200 high input or 3.100 second multiple input
Connection Type And Voltage Rating In Volts:
208.0 line to neutral low input or 220.0 line to neutral high input or 440.0 line to neutral second multiple input
Shaft End Characteristic:
A9 single style single end
Phase:
Three input
Frequency In Hertz:
50.0 input or 60.0 input
Terminal Type And Quantity:
9 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A271a0