NSN 6105-01-159-6148

Alternating Current Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6105-01-159-6148 **Thread Class:** 2b single end **Thread Direction:** Right-hand single end **Overall Height:** 36.250 inches **Overall Length:** 42.060 inches **Overall Width:** 25.000 inches Thread Length: 1.000 inches single end **Shaft Diameter:** 1.960 inches single end **Shaft Rotation Direction:** Clockwise single end or counterclockwise single end **Duty Cycle:** Continuous **Inclosure Feature:** Dripproof protected-15 deg Winding Type: Induction-squirrel cage **Mounting Method:** Fixed base **Mounting Facility Type And Quantity:** 4 unthreaded hole **Cooling Method:** Ambient air **Current Rating Method:** Load **Inclosure Specificationification: Features Provided:** Horizontal mounting position and vertical mounting position Frame Size Designation: 449tny **Power Rating:** 400.000 horsepower output

Thread Size:

0.500 inches single end

Length Of Shaft From Housing:

2.940 inches single end

NSN 6105-01-159-6148Alternating Current Motor - Page 2 of 2

Fiig: A271a0



Shaft Center To Mounting Surface Distance:
11.000 inches single end
Center To Center Distance Between Mounting Facilities Parallel To Length:
25.000 inches
Tempurature Rating:
50.0 operating degrees celsius
Rotor Speed Rating In Rpm:
3600.0 single no load
Center To Center Distance Between Mounting Facilities Parallel To Width:
18.500 inches
Current Rating In Amps:
450.000 single input
Connection Type And Voltage Rating In Volts:
440.0 line to neutral single input
Shaft End Characteristic:
A2 first style single end and a3 second style single end and a1 third style single end
Phase:
Three input
Special Features:
Shaft style a2 is 1.500 in. Diameter threaded double left-hand by 1.500 in. Lg, fit 3a; end of shaft w/4 holes 0.500 in. Diameter by 1.000 in
Dp, eql spaced
Frequency In Hertz:
60.0 input
Thread Series Designator:
Unf single end
Terminal Type And Quantity:
6 wire lead and 6 solderless lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No